

## HK...2RS Series

Seleccione	Consulta	Designacion	Principal Dimensions(mm)				Cr (N)	Cor (N)	Fatigue loading Cu (N)	Limitar la velocidad U/min	Peso gramo
			FW	D	C	r					
HK5024-2RS	50	58	24	0.8	3100	6300	8200	3600	81		
HK4016-2RS	40	47	16	0.8	14000	24300	3200	4500	37		
HK3520-2RS	35	42	20	0.8	18700	33500	4400	5000	41		
HK3516-2RS	35	42	16	0.8	13100	21300	2800	5000	32		
HK3024-2RS	30	37	24	0.8	22000	39500	5100	6000	44		
HK3020-2RS	30	37	20	0.8	17200	29000	3750	6000	36		
HK3016-2RS	30	37	16	0.8	12100	18200	23900	6000	31		
HK2820-2RS	28	35	20	0.8	16400	26500	3450	6000	34		
HK2530-2RS	25	32	30	0.8	25500	45000	5700	7000	47		
HK2524-2RS	25	32	24	0.8	19900	33300	4200	7000	40		
HK2520-2RS	25	32	20	0.8	15600	24000	3150	7000	31		
HK2516-2RS	25	35	16	0.8	11000	15200	1990	7000	27		
HK2220-2RS	22	28	20	0.8	13400	22100	2800	8000	26		
HK2216-2RS	22	28	16	0.8	9100	13400	1600	8000	18		
HK2020-2RS	20	25	20	0.8	12700	20100	2500	8500	23		
HK2016-2RS	20	26	16	0.8	8600	12100	1450	8500	18		
HK1816-2RS	18	24	16	0.8	8100	10900	1300	9500	15		
HK1625-2RS	16	22	25		9900	12300		10000	17		
HK1620-2RS	16	22	20	0.8	10900	15300	1900	11000	18		
HK1616-2RS	16	22	16	0.8	7600	9700	1160	11000	14		
HK1520-2RS	15	21	20	0.8	10500	14400	1780	11000	18		
HK1516-2RS	15	21	16	0.8	7800	9800	1190	11000	15		
HK1416-2RS	14	20	16	0.8	7100	8500	1010	12000	13		
HK1216-2RS	12	18	16	0.8	6500	7300	850	14000	11		
HK1014-2RS	10	14	14	0.4	4400	5100	650	17000	4.6		
HK0812-2RS	8	12	12	0.4	2750	2600	290	20000	3.3		
HK4520-2RS	45	52	20	0.8	21300	43000	5700	4000	54		
HK4020-2RS	40	47	20	0.8	2000	38500	5000	4500	48		

### HK...2RS Series

---

HK0810-2RS	8	12	10	0.4	2180	1930	265	20000	3.2
HK1012-2RS	10	14	12	0.4	3200	3350	380	17000	4.3