

1200 Series

Selecione Consulta		Designación de rodamiento	Dimensión [mm]				Capacidades de carga básica (kN)		Clasificaciones de velocidad (rpm)		Peso (Kg)
			D	D	B	rs min	Cr	Cor	Grasa	Petróleo	
1200	10	30	9	0.6	5.5	1.19	21000	24000	0.033		
1201	12	32	10	0.6	5.6	1.27	18000	22000	0.04		
1202	15	35	11	0.6	7.45	1.75	16000	19000	0.049		
1203	17	40	12	0.6	7.9	2.01	14000	17000	0.072		
1204	20	47	14	1	9.9	2.61	13000	15000	0.116		
1204K	20	47	14	1	9.9	2.61	13000	15000	0.114		
1205	25	52	15	1	12.1	3.3	11000	13000	0.138		
1205K	25	52	15	1	12.1	3.3	11000	13000	0.135		
1206	30	62	16	1	15.6	4.65	9200	11000	0.217		
1206K	30	62	16	1	15.6	4.65	9200	11000	0.213		
1207	35	72	17	1.1	15.8	5.1	8000	9400	0.317		
1207K	35	72	17	1.1	15.8	5.1	8000	9400	0.312		
1208	40	80	18	1.1	19.3	6.55	7100	8400	0.414		
1208K	40	80	18	1.1	19.3	6.55	7100	8400	0.407		
1209	45	85	19	1.1	21.9	7.35	6400	7500	0.457		
1209K	45	85	19	1.1	21.9	7.35	6400	7500	0.448		
1210	50	90	20	1.1	22.7	8.1	5800	6800	0.515		
1210K	50	90	20	1.1	22.7	8.1	5800	6800	0.504		
1211	55	100	21	1.5	26.8	10	5300	6200	0.692		
1211K	55	100	21	1.5	26.8	10	5300	6200	0.679		
1212	60	110	22	1.5	30	11.5	4900	5800	0.879		
1212K	60	110	22	1.5	30	11.5	4900	5800	0.864		
1213	65	120	23	1.5	31	12.5	4500	5300	1.13		
1213K	65	120	23	1.5	31	12.5	4500	5300	1.11		
1214	70	125	24	1.5	34.5	13.8	4200	4900	1.24		

1200 Series

1215	75	130	25	1.5	39	15.7	3900	4600	1.33
1215K	75	130	25	1.5	39	15.7	3900	4600	1.31
1216	80	140	26	2	40	17	3700	4300	1.65
1216K	80	140	26	2	40	17	3700	4300	1.62
1217	85	150	28	2	49	20.8	3500	4100	2.06