

RNA48 Series

Seleccione Consulta Designacion			Principal Dimensions				C	Co	Cu	nG	nB Peso
			FW	D	C	r					
RNA 4822	120mm	140 mm	30 mm	1 mm	106000 N	216000 N	36000 N	3750 U/min	2220 U/min	670 g	
RNA 4824	130 mm	150 mm	30 mm	1 mm	112000 N	239000 N	39000 N	3500 U/min	2030 U/min	730 g	
RNA 4826	145 mm	165 mm	35 mm	1,1 mm	134000 N	310000 N	48500 N	3150 U/min	1920 U/min	990 g	
RNA 4828	155 mm	175 mm	35 mm	1,1 mm	136000 N	325000 N	50000 N	2950 U/min	1800 U/min	1050 g	
RNA 4830	165 mm	190 mm	40 mm	1,1 mm	172000 N	400000 N	62000 N	2750 U/min	1750 U/min	1600 g	
RNA 4832	175 mm	200 mm	40 mm	1,1 mm	181000 N	435000 N	66000 N	2600 U/min	1630 U/min	1700 g	
RNA 4834	185 mm	215 mm	45 mm	1,1 mm	209000 N	510000 N	75000 N	2450 U/min	1550 U/min	1800	
RNA 4836	195 mm	225 mm	45 mm	1,1 mm	219000 N	550000 N	80000 N	2330 U/min	1430 U/min	2680 g	
RNA 4838	210 mm	240 mm	50 mm	1,5 mm	255000 N	690000 N	100000 N	2180 U/min	1290 U/min	3210 g	
RNA 4840	220 mm	250 mm	50 mm	1,5 mm	260000 N	720000 N	102000 N	1090 U/min	1220 U/min	3350 g	
RNA 4844	240 mm	270 mm	50 mm	1,5 mm	275000 N	790000 N	110000 N	1920 U/min	1080 U/min	3620 g	
RNA 4848	265 mm	300 mm	60 mm	2 mm	400000 N	1080000 N	150000 N	1730 U/min	940 U/min	5400 g	
RNA 4852	285 mm	320 mm	60 mm	2 mm	415000 N	1160000 N	158000 N	1620 U/min	860 U/min	5800 g	
RNA 4856	305 mm	350 mm	69 mm	2 mm	510000 N	1300000 N	175000 N	1500 U/min	810 U/min	9300 g	
RNA 4860	330 mm	380 mm	80 mm	2,1 mm	700000 N	1770000 N	235000 N	1380 U/min	710 U/min	12700 g	
RNA 4864	350 mm	400 mm	80 mm	2,1 mm	710000 N	1850000 N	242000 N	1310 U/min	660 U/min	13400 g	
RNA 4868	370 mm	420 mm	80 mm	2,1 mm	730000 N	1940000 N	247000 N	1240 U/min	620 U/min	14000 g	
RNA 4872	390 mm	440 mm	80 mm	2,1 mm	740000 N	2020000 N	255000 N	1180 U/min	580 U/min	14800 g	
RNA 4876	415 mm	480 mm	100 mm	2,1 mm	1130000 N	2900000 N	370000 N	1090 U/min	500 U/min	26000 g	