

RNA 49...RS Series

| Seleccione | Consulta | Designacion | Principal Dimensions(mm) | | | | Cr (N) | Cor (N) | Fatigue loading Cu (N) | Limitar la velocidad U/min | Peso gramo |
|------------|----------|-------------|--------------------------|-----|-------|-------|--------|---------|------------------------|----------------------------|------------|
| | | | FW | D | C | r | | | | | |
| | | | RNA4900-RS | 14 | 22 | 13 | | | | | |
| RNA4901-RS | 30 | 42 | 17 | 0.3 | 21800 | 24200 | 4550 | 6500 | 60 | | |
| RNA4902-RS | 35 | 47 | 17 | 0.3 | 23900 | 28500 | 5400 | 5500 | 69 | | |
| RNA4903-RS | 42 | 55 | 20 | 0.6 | 29500 | 39500 | 7200 | 4800 | 107 | | |
| RNA4904-RS | 25 | 37 | 17 | 0.3 | 19500 | 19900 | 3750 | 7500 | 56 | | |
| RNA4905-RS | 48 | 62 | 22 | 0.6 | 41000 | 53000 | 8800 | 4200 | 154 | | |
| RNA4906-RS | 35 | 47 | 17 | 0.3 | 23900 | 28500 | 5400 | 5500 | 69 | | |
| RNA4907-RS | 42 | 55 | 20 | 0.6 | 29500 | 39500 | 7200 | 4800 | 107 | | |
| RNA4908-RS | 48 | 62 | 22 | 0.6 | 41000 | 53000 | 8800 | 4200 | 154 | | |
| RNA4909-RS | 52 | 68 | 22 | 0.6 | 43000 | 59000 | 7900 | 3900 | 157 | | |
| RNA4910-RS | 58 | 72 | 22 | 0.6 | 45000 | 64000 | 10600 | 3500 | 160 | | |