

GF...DO



Seleccione	Consulta	Designacion	Dimensiones										l6	r1s min	Cr	Cor	Peso
			D	D	B	dk	d1	d2	h2	C1nom.	α						
GF20-DO	20 mm	35 mm	16 mm	29 mm	24,1 mm	50 mm	38 mm	19 mm	9 °	63 mm	0,3 mm	30000 N	65500 N	0,35 kg			
GF25-DO	25 mm	42 mm	20 mm	35,5 mm	29,3 mm	55 mm	45 mm	23 mm	7°	72,5 mm	0,6 mm	48000 N	68700 N	0,53 kg			
GF30-DO	30 mm	47 mm	22 mm	40,7 mm	34,2 mm	65 mm	51 mm	28 mm	6°	83,5 mm	0,6 mm	62000 N	115000 N	0,87 kg			
GF35-DO	35 mm	55 mm	25 mm	47 mm	39,7 mm	83 mm	61 mm	30 mm	6 °	102,5 mm	0,6 mm	80000 N	193000 N	1,5 kg			
GF40-DO	40 mm	62 mm	28 mm	53 mm	45 mm	100 mm	69 mm	35 mm	7 °	119 mm	0,6 mm	100000 N	305000 N	2,4 kg			
GF45-DO	45 mm	68 mm	32 mm	60 mm	50,7 mm	110 mm	77 mm	40 mm	7°	132 mm	0,6 mm	1217000 N	386000 N	3,4 kg			
GF50-DO	50 mm	75 mm	35 mm	66 mm	55,9 mm	123 mm	88 mm	40 mm	6°	149,5 mm	0,6 mm	156000 N	441000 N	4,4 kg			
GF60-DO	60 mm	90 mm	44 mm	80 mm	66,8 mm	140 mm	100 mm	50 mm	6°	170 mm	1 mm	245000 N	558000 N	7,1 kg			
GF70-DO	70 mm	105 mm	49 mm	92 mm	77,8 mm	164 mm	115 mm	55 mm	6°	197 mm	1mm	315000 N	724000 N	10,5 kg			
GF80-DO	80 mm	120 mm	55 mm	105 mm	89,4 mm	180 mm	141 mm	60 mm	6°	231 mm	1 mm	400000 N	804000 N	15 kg			
GF90-DO	90 mm	130 mm	60 mm	115 mm	98,1 mm	226 mm	150 mm	65 mm	5 °	263 mm	1 mm	490000 N	1352000 N	23,5 kg			
GF100-DO	100 mm	150 mm	70 mm	130 mm	109,5 mm	250 mm	170 mm	70 mm	7°	295 mm	1 mm	610000 N	1516000 N	31,5 kg			
GF110-DO	110 mm	160 mm	70 mm	140 mm	121,2 mm	295 mm	185 mm	80 mm	6°	332,5 mm	1 mm	655000 N	2340000 N	48 kg			
GF120-DO	120 mm	180 mm	85 mm	160 mm	135,5 mm	360 mm	210 mm	90 mm	6°	390 mm	1 mm	950000 N	3510000 N	75 kg			